

## ML4114 data logger

## Pro ML4000RH/T Series

Part of the **Hanwell Pro** ML4000RHT Series, the ML4114 combines high accuracy temperature and humidity measurement using an EE07 probe. The instrument includes LCD display and discreet design.

## **Features**

- √ Combined temperature & humidity measurement
- √ LCD display with data readings & battery life
- √ Superior performance hardware & high accuracy sensors
- √ Easily accessible battery & USB socket
- √ Logger memory capacity of 50,000 readings per channel
- √ Up to 3 year battery life
- √ Complies with RoHS, EU & WEEE directives
- √ Carries CE Marking

## **Typical Applications**

- · Dry storage
- · Ambient room conditions





Compatible with Hanwell EMS

Instrumentation specification	
Dimension (Excl. ancillaries)	110 x 80 x 35mm
Weight	200 grams
Power supply	1 x 3.6V AA Lithium battery
Battery life	Up to 3 years (depending on format of data retrieval)
Case material	ABS & PC
Memory capacity	50,000 readings per channel (unit can be set to wrap or stop when full)
Clock accuracy (logging)	20 ppm at <b>25°C</b>
IP Rating	IP30
Instrument measuring range	-20°C to +60°C if using an integral, onboard, probe -40°C to +60°C if using a compatible external probe, connected via an extension cable
Instrument operating range	-20°C to +60°C in a non-condensing RH environment
Instrument storage temperature	-40°C to +60°C
Resolution	0.1°C (temp), 0.1%RH (humidity)
Memory	4MB Flash











Product code: ML4114

Data Logger Functions	
Logging Intervals	Programmable from 10 seconds to 24 hours
Record Capacity	50,000 readings per channel
PC Interface	USB Communications
Software required	W200 – HanLog 4.5+ Software Package
Software compatibility	EMS - All Versions Synergy - All Versions RadioLog 8

Product codes	
88706	AA Lithium battery
Y119	Wall mounting bracket
Y055	USB Cable
Probe options	Please refer to the Hanwell Pro Sensor datasheet

**Manufactured by Ellab Monitoring Solutions** 









